



TPXCEL TRI-PURPOSE

The TPX - Tri-purpose diamond blade ensures that you have the correct diamond blade for the most common applications already mounted on your saw. The castellated segment design ensures quick stock clearance and a clean finish. In addition to its other attributes it also has ventilation cooling holes within the steel centre which allows for rapid heat dispersion.

KEY FEATURES

- Castellated Segments ensures quick stock clearance
- Laser Welded Segments
- Ventilated Steel Centre for rapid heat dispersion
- TCT Undercutting Protection protects joint between segment and blade



Mexco Diamond Blade product packaging



PRODUCT OVERVIEW:

Grade: XCEL Segment Height: 10mm Segment Attachment: Laser Welded Dry/Wet: Wet or Dry Use

Segment Type: Castellated Gullet Type: Keyhole Undercutting Protection: Yes

Recommended for: Angle Grinder, Disc Cutter, Bench Saw & Floor Saw



OPTIMUM COST PER CUT

The XCEL range of products are simply our best in class, due to an uncompromised use of raw materials in their manufacture they offer the user a cutting or drilling experience that is faster and cleaner with an optimum cost per cut.



PRODUCT DATA SHEET

DIAMETERS AVAILABLE:					
	Code	Diameter		Segment Width	Bore Size / s
		(mm)	(in)	(mm)	(mm)
	TPXCEL23022	230	9	2.8	22.23
	TPXCEL30020	300	12	3.2	20.00
	TPXCEL35020	350	14	3.2	20.00
	TPXCEL35025	350	14	3.2	25.40
	TPXCEL40020	400	16	3.5	20.00
	TPXCEL40025	400	16	3.5	25.40
	TPXCEL45025	450	18	3.6	25.40

SUITABLE FOR USE ON:



APPLICATION:



Will cut these materials with the possibility of reduced lifetime / glazing



Reinforced Concrete



Concrete Slabs



Concrete Block



Concrete Roof Tile



Asphalt

giazing

CONFORMS TO EN13236

Please note: Before using any cutting, grinding or drilling tool you should always consult your machine manufacturers hand book to establish the consumable tools suitability for the machine being used. Always wear the correct safety clothing and accessories before you commence use of the equipment.